



PVC Bundle Cable

ASSEMBLY :
UNTINNED ANNEALED COPPER, PVC INSULATED, CONDUCTORS CABLED,
OVERALL WRAPPED WITH COTTON YARN



TEMPERATURE RATING : 70°C

VOLTAGE RATING : 450/750V

SIZE : (1.11mm²) 7/0.45mm (AWG 18)

No. of Cores	Insulation (PVC) Thickness (mm)	Approx OD (mm)	Conductor Resistance Ohm/Km (25°C)	Insulation Resistance Mohm/Km (Min.)
3	0.65	5.71	18.46	10
4	0.65	6.40	18.46	10
5	0.65	7.16	18.46	10
6	0.65	7.95	18.46	10
7	0.65	7.95	18.46	10
8	0.65	8.75	18.46	10
9	0.65	9.57	18.46	10
10	0.65	10.60	18.46	10
11	0.65	10.60	18.46	10
12	0.65	11.01	18.46	10
13	0.65	11.46	18.46	10
14	0.65	11.70	18.46	10
15	0.65	12.05	18.46	10
16	0.65	12.46	18.46	10
17	0.65	12.89	18.46	10
18	0.65	13.25	18.46	10
19	0.65	13.25	18.46	10
20	0.65	14.06	18.46	10
30	0.65	17.76	18.46	10

The above color code is for reference only.
This information provides a general description of products and shall not form part of any contract.
Improvements or changes may be made to the products without advanced notification.